Pullover Sweater Front Worksheet

HEM

1._____Stitch gauge x_____One Half Bust/Chest =_____Sts to Cast On

SHAPE ARMHOLES

2. ____ Cast on Sts (Use answer from #1) - (____ Crossback x ____ Stitch gauge) = ____ Sts to be decreased at Armhole

3. _____ Sts to be decreased at Armhole ÷ 2 = _____ Sts to be decreased each side

4. _____ Sts to be decreased each side ÷ 2 = _____ Initial Bind Off

5. _____Armhole Depth - _____" Desired Neckline Depth =_____"

SHAPE V-NECK

6.(____Neck Measurement ÷ 2) x____Stitch Gauge =____ Front Neck Sts

7. _____Desired Neckline Depth x _____ Row Gauge = _____ Rows for Shaping

8. ____Front Neck Sts ÷ (____Rows for Shaping ÷ 2) = ____ Decrease Rows

SHAPE ROUNDED NECK (CREW OR U-NECK)

6.(____Neck Measurement ÷ 2) x____Stitch Gauge = ____ Front Neck Sts

7. .80 x____Front Neck Sts =____ Initial Bind Off

8. (____Crossback Stitches -____Initial Bind Off) ÷ 2 =____Shoulder Sts

9.((____Front Neck Sts x .20) ÷ 2) = ____Sts to Decrease Each Side